CVS4 - PRELIMINARY DATA



Product Description

The Tannoy CVS4 is a full bandwidth ceiling speaker system comprising a 100mm (4.00”) mid bass driver with a coaxially mounted 19mm (0.75”) high frequency section mounted in a vented, injection moulded, paintable front baffle manufactured from UV/weather resistant UL94V-0 ABS material.

The mineral loaded polypropylene cone material and nitrile rubber surround enhance durability and long-term reliability. This compact unit is specifically designed for all applications requiring the combination of excellent sonic quality for music and speech reinforcement and exceptional reliability.

The CVS4 is equipped with a low insertion loss 30W line transformer easily configurable to the following settings via front baffle mounted rotary tapping switch:

70V systems: 30W / 15W / 7.5W / 3.75W / OFF & low Impedance operation
100V systems: 30W / 15W / 7.5W / OFF & low Impedance operation

The CVS4 is supplied with an integral zinc-plated steel back can, with recessed termination box, to satisfy the vast majority of installation application requirements. The removable locking connector has screw terminals for secure wire termination and "loop through" facility. Strain relief is provided by a clamping mechanism for use with plenum rated cable or conduit. Security toggle clamps make for quick and easy installation, while two tile support rails and one C-ring are also included in the package. A plaster (mud) ring is available as an optional accessory.

Features

- 100mm (4.00") mineral loaded mid bass driver with coaxially mounted 19mm (0.75”) high frequency unit.
- Wide dispersion for optimum coverage.
- Easily accessible tapping switch on front baffle.
- Low insertion loss 30W line transformer
- Packaged with tile rails and C-ring for quick & easy installation and simple stocking logistics
- Safety agency ratings (pending) UL-1480, UL2043 and CE Five year warranty

Applications

- Multi-zone foreground music & paging systems
- Boardrooms & offices
- Business music systems
- Airports, convention centres, hotels
- Reception/ waiting rooms
- Houses of worship
- Retail outlets/ shopping malls
- Lounges/ bars
- Cruise ships
- Courtrooms

Tannoy United Kingdom	T: +44 (0) 1236 420199	F: +44 (0) 1236 428230	E: enquiries@tannoy.com
Tannoy North America	T: (519) 745 1158	F: (519) 745 2364	E: inquiries@tannoyna.com
Tannoy Deutschland	T: (04102) 888 393	F: (04102) 888 959	E: info@tannoy.com

tannoy.com

CVS4

TANNOY

TECHNICAL SPECIFICATIONS

System	CVS4
Frequency Response (-3dB) (1)	85Hz - 19kHz
Frequency Range (-10dB) (1)	77Hz - 22kHz
System Sensitivity (1W @1m) (2)	87dB (1W = 2.45V for 6Ω)
Nominal Coverage Angle	90 degrees conical
Coverage Angle (1kHz to 6kHz)	102 degrees
Directivity Factor (Q)	5.6 averaged 1kHz to 6kHz
Directivity Index (DI)	7.1 averaged 1kHz to 6kHz
Rated Maximum SPL	103dB (average) 109dB (peak)
Power Handling (3)	
Average	40W
Programme	80W
Peak	160W
Recommended Amplifier Power	80W @ 6Ω
Nominal Impedance	6Ω
Transformer Taps	
(via front rotary switch)	30W / 15W / 7.5W / 3.75W / OFF
70V	& low impedance operation
100V	30W / 15W / 7.5W / OFF & low impedance operation

Distortion		
1% Full Power	2nd Harmonic	3rd Harmonic
250Hz	0.231%	0.112%
1kHz	0.229%	0.253%
10kHz	0.163%	0.025%
10% Full Power	2nd Harmonic	3rd Harmonic
250Hz	0.99%	0.169%
1kHz	0.816%	0.323%
10kHz	0.444%	0.027%

Crossover Point	2.7kHz

Notes
(1) Average over stated Bandwidth. Measured in an IEC baffle in an Anechoic Chamber
(2) Unweighted Pink noise input, measured at 1m on axis"
(3) Long term power handling capacity as defined in EIA - 426B test

Transducers

Low Frequency	100mm (4.00") Mineral Loaded
High Frequency	19mm (0.75")

Physical

Enclosure	
Back can	Zinc plated steel
Baffle	Reflex loaded UL 94V-0 rated ABS
Grille	Steel, with weather resistant coating
Safety Features	Safety ring located at rear of enclosure for load bearing safety bond
Clamping Design	Security toggle clamp

Back Can Options

Cable Entry Options	Cable clamp & squeeze connector for conduit up to 22mm
Connectors	Removable locking connector with screw terminals with "loop through" facility
Safety Agency Ratings (pending)	UL-1480, UL-2043, CE
Hole Cutout Diameter	180mm
Dimensions	
Bezel diameter	213.0mm (8.39")
Front of ceiling to rear of back can	202.5mm (7.97")
Front of ceiling to top of safety loop	214.9mm (8.46")
Net Weight (ea)	2.60kg
Included Accessories	C Ring, tile bridge, paint mask, cutout template, grille
Optional Accessories	Plaster (mud) ring

Architectural Specifications

The Ceiling Monitor System shall consist of a 100mm (4.00") mineral loaded mid bass driver with coaxially mounted 19mm (0.75") high frequency unit mounted in a vented, injection moulded, paintable front baffle in UL94V-0 ABS material.

The back can shall be constructed of zinc plated steel. A recessed termination box shall be integrated with the back can, a removable locking connector with screw terminals for secure wire termination with "loop through" facility shall be provided. Strain relief will be provided by a clamping mechanism for use with plenum rated cable or conduit. A safety ring is located on the rear of the back can for a load bearing safety bond.

Performance of the ceiling monitor shall meet or exceed the following criteria: The system shall have a conical coverage pattern of 102 degrees (1kHz to 6kHz). Frequency response measured on axis shall be 85Hz - 19kHz (-10dB from rated sensitivity, measured in an IEC baffle in an anechoic chamber) with no equalization. Sensitivity shall be 87dB (1W @ 1m). Long term power handling capacity as defined in EIA-426B test shall be 40W, recommended amplifier power 80W. The nominal system impedance shall be 6 Ohm (in low impedance setting).

The Ceiling monitor system shall be equipped with a 30 Watt high performance line transformer for use in 70.7 or 100 Volt distributed audio systems with 30, 15, 7.5, 3.75 Watt taps available. An easily accessible rotary switch located on the front baffle shall be available for selecting transformer and low impedance settings. A weather resistant perforated steel grill covers the transducer and switch.

Two support rails and one C-Ring shall be included with the ceiling monitor system.

The front face diameter shall not exceed 213mm (8.39"); overall depth from the front of the ceiling to the top of the safety loop shall not exceed 214mm (8.46"). The template cut out size shall be 180mm (7.08").

The Ceiling Speaker System shall be the.....CVS4.

Tannoy United Kingdom | T: +44 (0) 1236 420199 | F: +44 (0) 1236 428230 | E: enquiries@tannoy.com
Tannoy North America | T: (519) 745 1158 | F: (519) 745 2364 | E: inquiries@tannoyna.com
Tannoy Deutschland | T: (04102) 888 393 | F: (04102) 888 959 | E: info@tannoy.com

tannoy©com