

Behringer WING Firmware Update

Version 3.1 (7 November 2025)

Added

- WING-DANTE expansion card can be used with AoIP-WSG module (use the following string for module registration: CRD-WDWSG). Check the “Behringer AoIP (Dante and WSG) module relocation instructions” document
- New compressor plugins: Even 88-COMP, LMT Compressor, One Knob Compressor
- New dual-band dynamic EQ plugin available in the Gate and Compressor slot
- Expanded noise gate and compressor selection available on Aux channels
- Direct inputs to Phones and Speakers monitoring buses
- Multiple Sources can be selected on the SOURCES screen by touch and drag. Parameter changes are applied to all selected Sources
- Preamp gain and phantom power accessible on the User Patches screen
- INIT/COPY toolbox includes Bus to Bus and Bus/Main to Matrix feeds
- Insert effects reset button without changing the processor model
- Setup > Surface > Fader/Screen Layer Link switch enables the main display and fader layer to show different channels
- Faster access to Custom Controls configuration screen by pressing the SETUP button twice
- WING COMPACT: Main Fader can be assigned to all channels
- WING COMPACT: new “Keep Main Fader” option
- WING COMPACT: DCA spill mode can be activated by pressing the SELECT button on the desired DCA
- USB 4-Track Recorder destination folder can be changed (REC PATH button)
- Return to the previous screen when a Custom Control assigned to a Fader or Overview screen is pressed a second time
- Bus Feed Configuration screen allows copying channel fader levels to sends levels

Changed

- All dynamic processors are available in both the Gate and Compressor slots
- Ducker plugin: increased HOLD time to 4000 ms
- Gate and Ducker plugins: added infinite RANGE

- Optimized Channel/Source colors for TFT displays and expanded color selection
- Increased maximum remote client number from 16 to 24. Make sure your network bandwidth supports this.
- Added channel names to Bus Feed Configuration screen
- Improved dynamics' crossover filters and visualization. Shaded area is compressed.
- Added notch filter to dynamics' sidechains
- Added option to stop SD recording when an error pop-up shows up
- Console initialization now overwrites parameters selected in the Global Safe screen
- Moved ALT Source switch from CONN to IN content category in the snapshot scope
- Auto Rider plugin: maximum HOLD time now shown correctly as "INF"
- Improved parameter resolution on some plugin parameters
- Graphic fixes on Pulsar EQ, Fortissimo 110 EQ and Source Extractor
- Firmware file name for WING/WING BK renamed to "wing-fullsize"

Fixed

- Tape Machine plugin frequency response
- NoStressor plugin introducing unwanted distortion at certain parameter combinations
- USB audio interface playback stopped after errors often caused by electrostatic discharges
- Sporadic issues with the USB audio interface at 44.1 kHz sample rate
- Graphic EQ fader selection using cursor buttons (WING/WING BK)
- Shimmer Reverb and Stereo Flanger: reset button
- CC channel solo button follows exclusive solo setting
- Wrong MIDI port #2 name string for WING Rack and Compact
- User Patch polarity ignored under specific conditions
- User Patch not following the mute status of the assigned Source